



Amerex Corporation

RUGGED

- 6 Year Warranty
- Stored Pressure Design
- Dependable Drawn Steel Cylinders
- Durable High Gloss Polyester Powder Paint
- All Metal Valve Construction
- Temperature Range -65°F to 120°F

USER FRIENDLY

- Easy and More Economical to Maintain and Service
- Large Loop Pull Pin
- Bar Coded and Bi-lingual Labels

OPTION

- USCG Approved with Bracket Listed on UL Label



Aluminum Valve
 A620T
 B403/T
 B409T
 B453
 B457
 A412



Brass Valve
 B462
 B447
 408



Available in Wheeled and Stationary Extinguishers

REGULAR extinguishers contain a siliconized sodium bicarbonate based dry chemical with free flowing and non-caking additives. Economical Class B & C protection with lower initial cost and recharging. This chemical smothers fires in flammable liquids and pressurized gases and will not conduct electricity back to the operator.

Largest selection of size and extinguisher options available

| AGENT TYPE | REGULAR DRY CHEMICAL | | | | | | | | |
|--------------------------|----------------------|--------------|---------|---------------|-------|---------------------|-------|-------|--------|
| VALVE TYPE | ANODIZED ALUMINUM | | | | | CHROME PLATED BRASS | | | |
| DESIGN | NOZZLE | | | HOSE & NOZZLE | | | | | |
| MODEL NUMBER | A620T | B403/B403T | B409T | B453 | B457 | A412 | B462 | B447 | 408 |
| UL & ULC RATING | 2B:C | 10B:C | 10B:C | 40B:C | 60B:C | 120B:C | 40B:C | 60B:C | 120B:C |
| CAPACITY (LBS.) | 1 | 2.5 | 5 | 5.5 | 10 | 20 | 6 | 10 | 20 |
| SHIPPING WT. (LBS.) | 2.5 | 5.5 | 9.25 | 9.75 | 18 | 38 | 13.75 | 19 | 39 |
| HEIGHT (IN.) | 10 | 15.5 | 15.25 | 15.25 | 20 | 24 | 16.25 | 20.25 | 24 |
| WIDTH (IN.) | 3.5 | 5.75 | 5.5 | 7.25 | 7.75 | 10.25 | 8.5 | 8.75 | 10.25 |
| DEPTH (IN.) | 2.63 | 3 | 4.25 | 4.25 | 5 | 7 | 5 | 5 | 7 |
| RANGE (INITIAL- FT) | 5-8 | 9-15 | 12-18 | 12-18 | 15-21 | 15-21 | 15-21 | 15-21 | 15-21 |
| DISCHARGE TIME (SEC.) | 10 | 10 | 10 | 14 | 18 | 28 | 14 | 18 | 28 |
| FM APPROVED | | YES | YES | | YES | YES | YES | YES | YES |
| OPTIONAL CHROME CYLINDER | YES | YES | YES | YES | YES | | YES | YES | |
| INCLUDED BRACKET | VEHICLE | WALL/VEHICLE | VEHICLE | WALL | | | | | |

Manufactured and Tested to ANSI/UL Standards
 Complies with NFPA 10 Standard
 ISO-9001 / ISO-14001 Certified
UL LISTED

CONFORMS TO TEST STANDARDS:

CAN/ULC-S504 - ANSI/UL299 &
 CAN/ULC-S508 - ANSI/UL711

MADE IN U.S.A.

REGULAR DRY CHEMICAL